



## Water Thinnable Sealer

Trubuild WTS 888 water thin able sealer is a single component water thinable polymeric liquid for sealing porosity of sand stone, concrete and other porous surfaces. Water can be added to any quantity depending upon porosity of the surface and gloss required

### APPLICATIONS

- As a sealer for sand stone, concrete & marble surfaces.
- Restore colour of terracotta tile.
- As sealer for wood to reduce the consumption of paint and clear lacquer
- Can be used on bricks
- Can be used above paint for gloss & waterproofing

### ADVANTAGES

- Acrylic emulsion which can be diluted with water.

### COVERAGE

- 8-10 sq. meter/kg/coat (Depend upon the porosity of the surface)

### STORAGE

Product should be stored in a dry place in their original, properly closed containers at temperature between 2-40°C. Partially emptied container should be closed immediately.

### TECHNICAL DETAILS

PROPERTIES	UNIT	RESULTS	METHOD
Physical State	Visual	Low Viscous Liquid	---
Appearance	Visual	Opaque	---
Colour	Visual	White	---
Drying Time	Minutes	15	---
Viscosity by Ford Cup-04	Sec	21	ASTM D 1200-2010
UV Resistance-500 hrs	Visual	No Colour Change	ASTM G 154-2016
Water Absorption Test			
Natural Stone – Control Sample	%	0.06	---
Natural Stone with Coating	%	Nil	---
Brick – Control Sample	%	16.33	---
Brick with Coating	%	10.28	---
Concrete- Control Sample	%	2.01	---
Concrete with Coating	%	1.32	---

# TRUBUILD WTS 888

Water Thinnable Sealer

TECHNICAL DATA SHEET

VER NO.1.2



## SHELF LIFE

24 months from the date of manufacturing.

## PACKING

1 kg & 5 kg

## HANDLING PRECAUTIONS

Mandatory and recommended industrial hygiene procedures should be followed whenever our products are being handled and processed. For additional information please consult the corresponding product data sheets and the brochure "Hygienic precautions for handling plastics products".

**IMPORTANT:** No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



### RESINOVA CHEMIE LIMITED

Registered Office: 207/1, 'Astral House', B/h Rajpath Club, Off S.G. Highway, Ahmedabad-380059, Gujarat, India.  
P: +91 79 6621 2000 | F: +91 79 6621 2121 CIN: U24295GJ2009PLC058120  
E-mail: [customercare@resinova.com](mailto:customercare@resinova.com) Website: [www.astraladhesives.com](http://www.astraladhesives.com)



MORE  
CONVENIENCE



FASTER  
FEEDBACK



ADDRESS TO  
TECHNICAL QUERY

Experience A Better Connect With The Company

Exclusively for our  
Channel Partners & Customers

Visit us at:

[wecare.astraladhesives.com](http://wecare.astraladhesives.com)